

BIG BLUE HOUSINGS

Filter Housings





BIG BLUE HOUSINGS

Filter Housings



FEATURES

- ▶ Types of cartridges: Ø: 4 1/2"
- ▶ Options:
 - pressure relief
 - bleed on inlet side of cap
- ▶ Maximum temperature: 37.8°C
- ▶ Maximum pressure: #10: 6.9 bar, #20: 6.2 bar
- ▶ Housing: polypropylene
- ▶ Cap: polypropylene (HFPP)
- ▶ Button assembly: 300-series stainless steel, EPDM, and polypropylene
- ▶ O-Ring: EPDM

PERFORMANCE CHARACTERISTICS

Model	Initial ΔP @ flow rate
3/4" #10 Big Blue	0.14 bar @ 57 Lpm
1" #10 Big Blue	0.07 bar @ 57 Lpm
1 1/2" #10 Big Blue	0.07 bar @ 76 Lpm
3/4" #20 Big Blue	0.14 bar @ 57 Lpm
1" #20 Big Blue	0.07 bar @ 57 Lpm
1 1/2" #20 Big Blue	0.07 bar @ 76 Lpm

PRODUCT SPECIFICATIONS

Model	Maximum dimensions	Inlet/outlet ports
#10 Big Blue	324 x 187 mm (13 1/8 x 7 1/4")	3/4" BSP or NPT
#10 Big Blue	338 x 189 mm (13 1/8 x 7 1/4")	1" BSP or NPT
#10 Big Blue	342 x 189 mm (13 5/8 x 7 1/4")	1 1/2" BSP or NPT
#20 Big Blue	585 x 187 mm (23 3/8 x 7 1/4")	3/4" BSP or NPT
#20 Big Blue	590 x 189 mm (23 3/8 x 7 1/4")	1" BSP or NPT
#20 Big Blue	603 x 189 mm (23 3/8 x 7 1/4")	1 1/2" BSP or NPT

WARNING: Protect against freezing to prevent cracking of the filter and water leakage.



The 150467, 150469 are tested and certified by NSF International to NSF/ANSI Standard 42 for material and structural integrity requirements.

All indicated Pentair trademarks and logos are property of Pentair. Third party registered and unregistered trademarks and logos are the property of their respective owners.

© 2025 Pentair. All rights reserved.